

# Power Rating Compressione

WAUKESHA 275GL					I.C. Water Temp. (Tcra) 54° C			800 rpm	900 rpm	1000 rpm
Model	Disp.	Bore & Stroke	C.R.	kWb	kWb	kWb				
16V275GL	285 L	275 x 300 mm	9:1	2686	3020	3356				
12V275GL	214 L	275 x 300 mm	9:1	2013	2267	2517				

WAUKESHA VHP					800 rpm	900 rpm	1000 rpm	1200 rpm
Model	Disp.	Bore & Stroke	C.R.	kWb	kWb	kWb	kWb	
P9390GSI	154 L	238 x 216 mm	8:1	984	1107	1230	1476	
P9390GL			10.5:1	984	1107	1230	1476	
L7044GSI	116 L	238 x 216 mm	8:1	835	940	1044	1253	
L7042GSI			8:1	736	828	920	1104	
L7042GL			10.5:1	736	830	920	1104	
L7042GL			10.5:1	—	—	920	1150	
L7042G			10:1	546	610	668	764	
L5794GSI			95 L	216 x 216 mm	8.2:1	686	772	858
L5794LT	10.2:1	—			—	901	1081	
L5774LT	10.2:1	—			—	795	954	
L5790G	10:1	450			501	550	630	
F3524GSI	58 L	238 x 216 mm	8:1	418	470	522	626	
F3514GSI			8:1	368	414	460	552	
F3521GL			10.5:1	367	413	459	550	
F3521G			10:1	273	305	334	384	

WAUKESHA VGF					1200 rpm	1400 rpm	1500 rpm	1600 rpm	1800 rpm
Model	Disp.	Bore & Stroke	C.R.	kWb	kWb	kWb	kWb	kWb	
P48GSI/GSID	48 L	152 x 165 mm	8.6:1	—	620	660	705	800	
P48GL/GLD			11:1	530	620	660	705	800	
P48GL/GLD			11:1	—	680	730	775	880	
L36GSI/GSID	36 L	152 x 165 mm	8.6:1	—	460	500	530	600	
L36GL/GLD			11:1	400	460	500	530	600	
L36GL			8.7:1	—	460	500	530	600	
L36GL/GLD			11:1	—	510	550	580	660	
H24GSI/GSID			24 L	152 X 165 mm	8.6:1	—	310	330	355
H24GL/GLD	11:1	265			310	330	355	400	
H24GL	8.7:1	—			310	330	355	400	
H24GL/GLD	11:1	—			340	365	390	440	
H24G	11:1	160			186	198	213	239	
F18GSI/GSID	18 L	152 x 165 mm	8.6:1	—	230	250	265	300	
F18GL/GLD			11:1	200	230	250	265	300	
F18GL			8.7:1	—	230	250	265	300	
F18GL/GLD			11:1	—	255	275	290	330	
F18G			11:1	119	138	149	160	179	

TEDOM					1500 rpm	1800 rpm
Model	Disp.	Bore & Stroke	C.R.	kWb	kWb	
TG 170 DV NX86	11,946	130 x 150 mm	12:1	170,0	—	
TG 100 DV NX86	11,946	130 x 150 mm	12:1	98,8	—	

For other power output pls. contact us with more details